

Zero Turn Specifications		3900 Series 28 - 61	3000 Series 22 - 52	2900 Series 27 - 48	
<b>ENGINE</b>	Make & Model	Vanguard™ Big Block™ V-Twin	Kawasaki - FX651	Briggs & Stratton Professional Series™	
	Gross Horsepower/Cylinders	28-gross hp* / 2	22-gross hp** / 2	27-gross hp* / 2	
	Muffler	Canister	Canister	Canister	
	Spin-on Oil Filter	Yes	Yes	Yes	
	Choke/Throttle	Separate Levers	Separate Levers	Separate Levers	
	Fuel Tank Capacity	6.0 U.S. Gal.	6.0 U.S. Gal.	6.0 U.S. Gal.	
	Battery (cca)	340cca	340cca	340cca	
<b>TRANSMISSION</b>	Make	Hydro-Gear® ZT-5400	Hydro-Gear® ZT-5400	Hydro-Gear ZT-3100	
	Type	Hydro Transaxles	Hydro Transaxles	Hydro Transaxles	
	Forward Speed (MPH)	0 - 10.0	0 - 10.0	0 - 8.0	
	Reverse Speed (MPH)	0 - 5.0	0 - 5.0	0 - 4.0	
	Brakes	Internal	Internal	Internal	
	<b>CHASSIS</b>	Frame	2" x 2" x 3/16" frame rails	1 1/2-Gauge 1.5" x 2" frame rails	1 1/2-Gauge 1.5" x 2" frame rails
Front Axle		Fabricated, Greaseable tapered caster spindle and tapered wheel bearings	Fabricated, Greaseable tapered caster spindle and tapered wheel bearings	Fabricated, Greaseable tapered caster spindle and tapered wheel bearings	
Front Smooth Tread Tires		13.00 x 6.00 - 6.5	13.00 x 5.00 - 6	11.00 x 4.00 - 5	
Rear Turf Saver Tires		24.00 x 12.00 - 12	22.00 x 11.00 - 10	20.00 x 10.00 - 10	
Seat		Molded Premium	Molded Premium	Molded Premium	
<b>MOWER</b>		Cutting Width, # of Blades	61", 3-blade, fabricated	52", 3-blade, fabricated	48", 3-blade, fabricated
	Height-of-Cut Adjustment	.25" increments	.25" increments	.25" increments	
	Height-of-Cut Range (in)	1.5 - 4.5	1.5 - 4.5	1.5 - 4.5	
	Mower Lift	Foot controlled	Foot controlled	Foot controlled	
	Discharge Deflector	Rubber, Pivoting	Rubber, Pivoting	Rubber, Pivoting	
	Gauge Wheels	Standard	Standard	Standard	
	<b>FEATURES</b>	Steering	Twin-Lever	Twin-Lever	Twin-Lever
		Parking Brake	Separate Lever	Separate Lever	Separate Lever
		Hourmeter	Standard	Standard	Standard
		PTO Switch	Standard, Electric	Standard, Electric	Standard, Electric
<b>ATTACHMENTS/ ACCESSORIES</b>	Headlights	Optional	Optional	Optional	
	Mulching Kit	Optional	Optional	Optional	
	Triple Bag Grass Collector	Optional - 10-bushel capacity	Optional - 10-bushel capacity		
	Twin Bag Grass Collector			Optional - 7-bushel capacity	
	Dump Cart	N / A	N / A	N / A	
	Trailer Hitch	Optional	Optional	Optional	
	Flat Free Caster Tire	Optional	Optional	Optional	
	Seat Arm Rests	Standard	Standard	Optional	
	Stripe Kit	Standard	Standard	Optional	
	<b>DIMENSIONS</b>	Length (in)	79	78	69
Width*** (in includes discharge)		76	68	64	
Height (in)		69.5	70.5	41.5	
Wheel Base (in)		59	50	43	
Weight(lbs)		1171	1141	724	
<b>WARRANTY</b>		Residential Use (Machine/Engine)	2/2 - Years Ltd.	2/2 - Years Ltd.	2/2 - Years Ltd.
	Commercial Use (Machine/Engine)	90 Days/1-Year Ltd.	90 Days/1-Year Ltd.	90 Days/1-Year Ltd.	

Zero Turn Specifications		24 - 46	2300 Series 26 - 52	21 - 42	
<b>ENGINE</b>	Make & Model	Briggs & Stratton Professional Series™ V-Twin w/Electronic Fuel Management	Briggs & Stratton Professional Series™ V-Twin	Briggs & Stratton Professional Series™	
	Gross Horsepower/Cylinders	24-gross hp* / 2	26-gross hp* / 2	21-gross hp* / 2	
	Muffler	Clam Shell/Under Frame	Clam Shell/Under Frame	Clam Shell/Under Frame	
	Spin-on Oil Filter	Standard	Standard	Standard	
	Choke/Throttle	Single Lever - EFM	Choke-a-Matic	Choke-a-Matic	
	Fuel Tank Capacity	3.0 U.S. Gal.	3.0 U.S. Gal.	3.0 U.S. Gal.	
	Battery (cca)	230cca	230cca	190cca	
	<b>TRANSMISSION</b>	Make	Hydro-Gear® ZT-2800R	Hydro-Gear® EZTR	Hydro-Gear® EZTR
		Type	Sealed Hydro Transaxle	Sealed Hydro Transaxle	Sealed Hydro Transaxle
Forward Speed (MPH)		0 - 6.0	0 - 6.0	0 - 6.0	
Reverse Speed (MPH)		0 - 3.0	0 - 3.0	0 - 3.0	
Brakes		Internal COG	External COG	External COG	
<b>CHASSIS</b>		Frame	12-Gauge one-piece formed steel	12-Gauge one-piece formed steel	12-Gauge one-piece formed steel
	Front Axle	Cast Iron, 1-inch spindle shafts	Cast Iron, 5/8-inch spindle shafts	Cast Iron, 5/8-inch spindle shafts	
	Front Smooth Tread Tires	11.00 x 4.00, 2-ply	11.00 x 4.00, 2-ply	11.00 x 4.00, 2-ply	
	Rear Turf Saver Tires	20.00 x 10.0/ 2-ply K500	18.00 x 9.5/ 2-ply K500	18.00 x 8.5/ 2-ply K500	
	Seat	5-position w/ arm rests	5-position w/ arm rests	Low Profile	
	<b>MOWER</b>	Cutting Width, # of Blades	46", 3-blade, 12-Gauge	52", 3-blade, 14-Gauge	42", 2-blade, 13-Gauge
Height-of-Cut Adjustment		Infinite	Infinite	Infinite	
Height-of-Cut Range (in)		1.5 - 3.75	1.5 - 3.75	1.5 - 3.75	
Mower Lift		Electric	Electric	Electric	
Discharge Deflector		Plastic, Pivoting	Plastic, Pivoting	Plastic, Pivoting	
Gauge Wheels		Standard, Front & Rear	Standard, Front & Rear	Standard, Front & Rear	
<b>FEATURES</b>		Steering	Twin-Lever	Twin-Lever	Twin-Lever
		Parking Brake	Separate Lever	Separate Lever	Separate Lever
		Hourmeter	Standard	Standard	Standard
		PTO Switch	Standard, Electric	Standard, Electric	Standard, Electric
<b>ATTACHMENTS/ ACCESSORIES</b>	Headlights	N/A	N/A	N/A	
	Mulching Kit	Optional	Optional	Optional	
	Triple Bag Grass Collector	Optional - 10-bushel capacity	Optional - 10-bushel capacity	Optional - 10-bushel capacity	
	Twin Bag Grass Collector				
	Dump Cart	Optional - 10-cu ft	Optional - 10-cu ft	Optional - 10-cu ft	
	Trailer Hitch				
	Flat Free Caster Tire				
	Seat Arm Rests	Standard	Standard		
	Stripe Kit				
	<b>DIMENSIONS</b>	Length (in)	75	75	75
Width*** (in includes discharge)		55	61	52	
Height (in)		39	39	39	
Wheel Base (in)		48	48	48	
Weight (lbs)		590	554	554	
<b>WARRANTY</b>		Residential Use (Machine/Engine)	2/2 - Years Ltd.	2/2 - Years Ltd.	2/2 - Years Ltd.
	Commercial Use (Machine/Engine)	90 Days/1-Year Ltd.	90 Days/1-Year Ltd.	90 Days/1-Year Ltd.	